

In-store impulse-generating merchandiser

Multi Deck 60- 4 level



With the upright, self serve Fri-Jado Multi Deck, your customers can pick up delicious, hot pre-packaged snacks and meal solutions practically anywhere in the store. It features four levels, which allows you to stock numerous products and reduce the need for re-stocking.

Hot air is being blown from the front of the shelf and circulates within the shelf surface resulting in an optimum air circulation around the hot product.

Large glazed walls creating a 180-degree view and products at eye-level in an appealing design create an outstanding product presentation and boost impulse sales.


Features MD 60 - 4 Essential

Top features

- Self serve heated Multi Deck display
- Attractive presentation that boosts impulse sales
- Patented Hot Blanket holding technology keeps products warm
- Customizable price strips

Standard characteristics

- 60 cm wide - 4 level display
- Product temperature maintained at 65°C
- Ideal for chicken, wraps, snacks, soups etc.
- Upright design saves space
- Offers merchandising opportunities throughout the store
- Total display capacity of 0.95 m²
- Footprint of 0.45 m²
- Clear side glass and angled shelves provide optimal product visibility
- Shatter-resistant clear side glass for optimum safety and insulation
- Saves up to 20% on energy by air-curtain technology on each shelf
- Safe holding temperature for up to four hours
- Angled shelves, safe to touch
- Price strips on each shelf
- Front bumpers to protect from shopping carts
- 98% recyclable (environmentally friendly)
- Plug-and-play




Safe-to-touch angled shelves



Price strips per shelf



180-degree product view



Keeps hot food at 65°C

MD 60-4 Essential

Dimensions

Width	620 mm
Depth	968 mm
Height	1912 mm

Technical data

Net weight	250 kg
Gross weight	294 kg
Voltage	1N~230 V
Frequency	50/60 Hz
Power	3.2 kW

Specifications and technical data are subject to amendment without notice.

These are basic drawings. For more detailed technical information, please refer to the installation manual at www.frijado.com.

Patent number: EP2309897

