




Legend

- Cabinet outline
- Optional cabinet outline
- Underframe outline
- Condensing unit outline
- Electronics outline
- Humidification system outline
- Space reserved for connections

D = Drain connection (Ø 1 1/2")  
E = Electrical supply (see notes)  
W = Water supply (min. 29 psi)  
R = Refrigeration connection (see notes)



Notes

- These are general drawings, individual counter configurations may differ
- Always check the corresponding Custom Counter Configuration document for the exact counter specifications and the required electrical supply
- Self-contained counters can be supplied with an optional evaporation tray in which case a permanent drain connection is no longer required
- A fixed water supply is only required in case the cabinet is supplied with an optional humidification system
- Space underneath the cabinet may be used for ambient or refrigerated understorage depending on the cabinet configuration, always use the connection points as indicated
- Counters should be installed according to local laws and regulations
- Contact Fri-Jado or your local distributor in case of any questions

Top elevations

Custom Counter FreshCold 30 (self-contained)

Not available

Custom Counter FreshCold 40 (self-contained)

Custom Counter FreshCold 50 (self-contained)

Custom Counter FreshCold 60 (self-contained)

Customer side

Custom Counter FreshCold 70 (self-contained)

Customer side

Custom Counter FreshCold 80 (self-contained)

Customer side

Custom Counter FreshCold 90 (self-contained)

Customer side

Custom Counter FreshCold 100 (self-contained)

Customer side

Custom Counter FreshCold 110 (self-contained)

Customer side

Custom Counter FreshCold 120 (self-contained)

Customer side

Custom Counter FreshCold 130 (self-contained)

Not available

Custom Counter FreshCold 140 (self-contained)

Not available

Custom Counter FreshCold 150 (self-contained)

Not available