

Doc. nr. 9124589	Rev. 0	Registration form. MCC Drop in installation instruction	
----------------------------	------------------	---	--

MCC Hot version:

Important remark before installation:

When installing Front doors on the drop in unit, Please follow Front door installation procedure (under construction), until the step in which the glass must be placed.

Placing the doors in a later stage, means the unit must be lifted again.

Installation must comply with:

- Make sure that the furniture is still easily accessible for service after installation by means of a removable hatch.
- Provide enough space to place the furniture with a stacker.
Maintain the dimensions and minimum height as indicated in the installation manual.
- Provide adequate ventilation; keep the minimum air inlet and outlet opening as indicated on the last page.
- Make sure that the room / shop in which the furniture is placed meets the minimum dimensions as indicated in the installation manual.
- All warning signs / labels, minimum floor area label and Data plate must remain visible after installation.
- Operation of the appliance must be accessible.

Doc. nr. 9124589	Rev. 0	Registration form. MCC Drop in installation instruction	
----------------------------	------------------	---	--

MCC Cold version:

Important remark before installation:

When installing Front doors on the drop in unit, Please follow Front door installation procedure (under construction), until the step in which the glass is put in.

Placing the doors in a later stage, means the unit must be lifted again.


Installation must comply with:

- No spark-forming components or components with a high surface temperature may be present in the substructure / counter where the furniture is placed.
- The refrigeration components must not be directly accessible by unauthorized Personnel.
- Make sure that the furniture is still easily accessible for service after installation by means of a removable hatch. The condenser must be cleaned regularly.

Keep enough space on the back of the unit, to enable servicing which implies the back panel of the furniture can be removed.


- Provide enough space to place the furniture with a stacker.
Maintain the dimensions and minimum height as indicated in the installation manual.
- Provide adequate ventilation; keep the minimum air inlet and outlet opening as indicated in the installation manual. Place baffles to prevent hot exhaust air from being sucked back through the condenser.
- Make sure that the room / shop in which the furniture is placed meets the minimum dimensions as indicated in the installation manual.
- Make sure that the warning signs / labels are / remain visible after installation.
- Operation of the appliance must be accessible.
- Additional ventilation: prevent gas accumulation due to leakage. Used gas is heavier than air.
- Avoid high temperatures in the vicinity of the furniture.

Doc. nr. 9124589	Rev. 0	Registration form. MCC Drop in installation instruction	
----------------------------	------------------	---	--



Step 1.


Position the cabinet above the cut-out in the counter top with a forklift and support it using the wooden beams supplied with the unit



Step 2.


Lift the cabinet from below, using stable filler blocks and remove the wooden support beams

Doc. nr. 9124589	Rev. 0	Registration form. MCC Drop in installation instruction	
----------------------------	------------------	---	--



Step 3.




Apply sealant or a thin flexible foam seal around the cut-out in the countertop. Carefully lower the cabinet into the counter



Step 4.

Remove and discard the metal transportation frame.


Doc. nr. 9124589	Rev. 0	Registration form. MCC Drop in installation instruction	
----------------------------	------------------	---	--


	<p>Step 5.</p> <p>Install the control panel using the supplied mounting plate and screws. (up to 1 meter from the original position)</p>
	<p>Step 6.</p> <p>Install a partition panel to prevent recirculation of hot condenser air. (refrigerated models only)</p>
	<p>Step 7.</p> <p>Install all remaining trim panels. Make sure ventilation openings have the correct size and the cabinet remains accessible for service and maintenance.</p>

Doc. nr. 9124589	Rev. 0	Registration form. MCC Drop in installation instruction	
----------------------------	------------------	---	--




Make sure, after build in, the cool engine is still accessible.

Keep in mind the complete cool engine is extendable at the back side of the unit for maintenance and service purposes.





Control panel cut-out dimensions

Partition panel dimension
(only required for refrigerated units)



Worktop cut-out dimensions

Legend

x:	Cabinet length
d:	Cabinet depth
d1:	Counter depth in front of the cabinet
d2:	Counter depth behind the cabinet
x1:	Counter length left of the cabinet
x2:	Counter length right of the cabinet
h:	Counter height (min. 500)
t:	Worktop thickness

Table

	x	d	A1	A2
MCC-90-3 C	SS	900	750	1100
MCC-120-3 C	SS	1200	750	1250
MCC-150-3 C	SS	1500	750	1250
MCC-90-3 C	FS	900	750	500
MCC-120-3 C	FS	1200	750	500
MCC-150-3 C	FS	1500	750	500
MCC-90-3 H	SS	900	750	n.a.
MCC-120-3 H	SS	1200	750	n.a.
MCC-150-3 H	SS	1500	750	n.a.
MCC-90-3 H	FS	900	750	n.a.
MCC-120-3 H	FS	1200	750	n.a.
MCC-150-3 H	FS	1500	750	n.a.
MCC-90-3 H	FS	900	750	n.a.
MCC-120-3 H	FS	1200	750	n.a.
MCC-150-3 H	FS	1500	750	n.a.

REVISION	REV. DATE	REMARK	Rev. principle	Surface treatment	Draw. tolerance
INTERNAL					
INTERNAL	INT. NUMBER	DRAMA	van Bergen	APPROVED	
	MUT nm	STATUS	In Progress	DATE	08.10.2020
	A	SCALE	1:20	PRODUCT	9124554
		VIEWES			
	DESCRIPTION	Initialation instructions MCI drop-in		INT. NUMBER	9124554
				REV.	A3