INSTRUCTION MODIFICATION KIT IGNITION STG 7 P GAS
PART NUMBER 9172201S

This documentation can also be found in the service manual STG 7 P gas fired rotisserie oven, page 11 until 22.

IGNITION/IONISATION SET ON COUPLING TUBE

1. Remove the right side panel according prior procedure.
2. Remove the wiring from the set on the gas burner safety control.
3. Remove the nuts that secure the set and remove the set. Replace the gasket.
4. Remove the nuts and bolts that secure the coupling tube and remove the tube. Replace the gaskets.
5. Connect A to A , B to B and C to C. , the fastons for B and C are the same,(2.8 mm) the faston for A is bigger (4.8 mm).

6. Remove the top plate above the exhaust pipe.
7. Change the insulation of the exhaust pipe. Insulation is fitted with 2 springs.
8. Reverse the procedure to install.

Mount the blower in the middle under the drive motor and connect the wiring. see next pages.

Change the reset switch.

VERSION FOR USA

VERSION FOR EUROPE

Kit 9172201S consists of the following parts:

2x 9292103	Gasket, burner 4 mm
1x 9172183	Gasket 4 mm
1x 9170587	Coupling tube
1x 9172198	Gasket, ignition set
1x 9172200	Ignition/ionisation set
1x 9292107S	Insulation exhaust pipe, incl. 2 springs
1x 2005797	Faston 4,8 mm for ignition set
2x 2005836	Faston 2,8 mm for ignition set
1x 3500031	Blower
1x 9294200	Mounting plate, blower
2x 2005705	Receptacle for blower
3x 4285084	Bolt, selfdrilling
1x 4289966	Nylon spacer
4x 4285135	Taptite
1x 9171057	Reset switch