

# In-store impulse-generating merchandiser

Multi Deck 120 - 5 levels  
Essential



**The Fri-Jado Multi Deck boosts hot food-to-go sales with an irresistible product presentation. It can be used anywhere in the store to stimulate customers to pick up hot grab-and-go products. Thanks to its square, upright design, it lines up smoothly with other equipment and uses only limited floor space.**

Our patented Hot Blanket holding technology controls food safety. Hot air is blown from the front of the shelf and circulates over the shelf surface, after which it is recycled into the unit. Your products are completely surrounded by a blanket of hot air, ensuring an even holding temperature.

Large, transparent side panels provide a 180-degree view on your products. The appealing design provides an outstanding product presentation which is sure to boost impulse sales.

## Features MD 120 - 5 Essential

### Top features

- Square design - square glass, black canopy
- Interchangeable price strips on each shelf
- Hot Blanket holding technology - keeps products warm at 65° for at least 4 hours
- Endless possibilities - ideal for chicken (portions), panini, pies, pastries, soups, hot rolls, wraps etc.

### Standard characteristics

- Self serve heated Multi Deck display unit
- 120 cm wide - 5 level display
- Total presentation area of 2.54 m<sup>2</sup>
- Footprint of 0.88 m<sup>2</sup>
- Solid back
- Angled shelves provide optimum product visibility
- Shatter-resistant clear side glass for optimum safety
- Front bumpers to protect from shopping carts
- Saves up to 20% on energy by air-curtain technology on each shelf
- 98% recyclable (environmentally friendly)
- Plug-and-play

### Accessories

- Customer-side temperature indicator
- Shelf leveler




Optimum product visibility



Stylish black canopy



Square glass



Keeps hot food at 65°C

## MD 120-5 Essential

1 Power cable, 2.5 m

### Dimensions

Width	1200 mm
Depth	790 mm
Height	1972 mm

### Technical data

Net weight	300 kg
Gross weight	353 kg
Voltage	3N~ 400/230 V
Frequency	50/60 Hz
Power	6.5 kW

Specifications and technical data are subject to amendment without notice.

These are basic drawings. For more detailed technical information, please refer to the installation manual at [www.frijado.com](http://www.frijado.com).

